



TEBER-II 30/40 Technical Specifications

Data subject to change without notice.

GENERAL	
Turret Type	TEBER-II 30/40 Two Man Turret
Main Armament	30mm/40mm Chain Gun, Dual Feed Automatic Cannon (can be replaced with a 30 or 40mm barrel, without making any changes to the gun mount and other parts)
Number of Ready to Fire Rounds	310
Secondary Armament (Coaxial)	7.62 mm MG
Number of Ready to Fire Rounds	1200 (7.62 mm)
Anti-Tank Guided Missile	2 ea ready to fire ATGM (various types of modern anti-armour systems selected by the user)
Traverse	360° Continuous
Elevation	-10° to +45°
Max Rotation Speed	> 60°/sec Traverse & Elevation
Max Acceleration	> 1.5 rad/s ² (Tra/El)
Tracking Rate	0.3 mil/sec
Stabilisation	Electric Drive with Two-Axis
Overhead 7.62 mm RCWS with Commander Sight	Optional
• Armament	7.62 mm or 5.56 mm MG
• Number of Ready to Fire Rounds	800 (5.56mm), 500 (7.62mm)
• Traverse	360° Continuous
• Elevation	-50° to +85°

SIGHT & FIRE CONTROL SYSTEM	
Thermal Imager	
Daylight Camera	
Laser Range Finder	
Automatic Target Tracking	
Low Ammunition Warning System	
Electronic Image Stabilisation	
Moving Target Indication	
Automatic Ballistic Computing	
Gunshot Detection System	
Gunner's Optical Back-up Sight	
Commander's Panoramic Sight	
Fire Control Computer	

WEIGHT & DIMENSIONS	
Combat Weight	<4,050 kg
Combat Weight with ATGM	<4,400 kg
Ring Gear Diameter	1,600 mm
Swing Radius	3,420 mm
Width	2.95 m
Height	0.7 m

PROTECTION	
All Around Ballistic Protection	STANAG 4569 (Level Classified)
Smoke Grenade Dischargers	Optional



FNSS Savunma Sistemleri A.Ş.
Ogulbey Mahallesi Kumludere Caddesi No: 11 Golbasi 06830 Ankara - Türkiye
T +90 (312) 497 43 00 F +90 (312) 497 43 01 - 02

www.fnss.com.tr
f y x in @ e

www.fnss.com.tr
f y x in @ e



TEBER-II 30/40

MEDIUM CALIBER TWO-MAN TURRET



OVERVIEW

The TEBER-II 30/40 TMT (Two-Man Turret), is a medium caliber turret that can be fitted to wheeled and tracked armoured vehicles and is offered in two configurations. In the conventional two-man configuration, the commander and the gunner are positioned in the turret basket.



Although the turret basket occupies a considerable amount of space inside the vehicle, the manned configuration provides significant advantages to the vehicle commander in terms of situational awareness, fire control efficiency and effective control of the battlefield. Communication between the gunner and the commander is more effective and accurate.

The TEBER-II 30/40 TMT incorporates the latest technologies in turret drives, fire control, protection, and lethality. It can operate day and night under all weather conditions and battle environments thanks to its integrated sensors and other electronic systems. Both the gunner and the commander are able to control all functions of the turret. Additionally, thanks to the manual backup system, the gunner can aim the gun with its backup optical site and steer the turret in traverse and elevation and engage the targets.

The main armament consists of the Mk44 30 mm dual-feed automatic cannon with 310 ready-to-fire rounds and has a maximum rate of fire of 100 rounds/minute.

Two types of ammunition can be loaded in the double ammunition box of the turret feed and ensure the neutralization of various kinds of targets. Different types of ammunition can be used in the main armament, primarily high explosive, anti-armour or programmable airburst ammunition. In particular, programmable ammunition ensure that detected targets can be engaged in the most effective way. The 30 mm automatic cannon and coaxial machine gun provide the ability to effectively engage a wide spectrum of targets.

SuperShot 40 mm (40x180 mm) ammunition can also be used in the turret as the 30 mm cannon can be easily converted by a simple replacement on the field to fire those 40 mm rounds.



TEBER-II 30/40

MEDIUM CALIBER TWO-MAN TURRET



Two each ATGM missiles are integrated to both sides of the turret. According to user requirements, various modern anti-armour systems (ATGM's) such as Semi-automatic command to line of sight (SACLOS) and Automatic command to line of sight (ACLOS) guided missile can be integrated on turret's modular ATGM launcher. Two ATGM launchers can be operated separately as well giving the user to opportunity to elevate at different angles to fulfill requirements of most common ATGM missiles on the market.

The coaxial weapon consists of a 7.62 mm machine gun with 1,200 ready-to-fire rounds.

Two banks of four 76 mm grenade launchers (total 8) are mounted on both sides of the turret ensuring maximum coverage. These can be replaced by grenade launchers of other calibres according to customers' requirements.

The gun turret drive system is electrical, with two-axis stabilisation ensuring high accuracy even when firing on the move. The turret can rotate seamlessly on the 360°, the elevation arc being from -10° to +45°, angular speed being over 60°/second.

The TEBER-II 30/40 TMT has an advanced fire control capability thanks to its on-board fire control computer and the two-axis stabilised independent sighting system. It can generate a real time kinematic lead and super elevation solution with superior automatic target tracking capability based on the range. Thanks to these features TEBER-II 30/40 TMT offers first-round-hit probability for stationary/moving targets, which also ensures a more effective ammunition use.

The dual-axis stabilised sight system includes a long-wave or mid-wave thermal imager, a day camera with wide and narrow field of view angles and a laser range finder. The sight is also fitted with an automatic tracking system.

On top of the TEBER-II 30/40 TMT we also find a two-axis stabilised 360° commander's panoramic sight with thermal imager, day camera and laser range finder enabling hunter-killer capability.

The commander's panoramic sight can optionally be replaced with an Overhead Remote Controlled Weapon Station (ORCWS). The ORCWS acts as the commander's panoramic sight that can rotate 360° continuously on the traverse axis while enables engaging targets independent form the turret's position with 7.62 mm or 5.56 mm weapon equipped. Its high elevation is used against threats on high grounds on urban environment (building, roofs, etc.) as well as encountering drones approaching from top angles. Sight systems include a long- or mid-wave thermal imager, wide and narrow angle day sensors and a laser range finder.

Thanks to the independent power source integrated in the turret and to the user-configurable intelligent power distribution system, the turret drive, gun firing, and sighting systems can be electronically used for a longer time while in emergencies, regardless of the vehicle battery status. The TEBER-II 30/40 TMT shell is made of all-welded aluminium armour with add-on composite and steel armour providing ballistic protection up to user requirement.



Watch the Video